

999.00 EUR

incl. 19% VAT, plus [shipping](#)



- Intel® Apollo Lake N3350/N4200 Processor
- 1 \* SO-DIMM Dual CH DDR3L up to 8GB
- 2 \* USB3.0, 6 \* RJ45, 1 \* RS232(RJ45 TYPE)
- M/B Form Factor : Mini ITX (170x170mm)
- 1U FLEX POWER\_200W

|                 |                                                                                                                                                                                                                                                                                                    |                     |                     |                                     |                                                 |
|-----------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------|---------------------|-------------------------------------|-------------------------------------------------|
| MB Model        | – JNF692G6-335 / JNF692G6-420 (Mini-ITX)<br>– JNF692G6-335B1 / JNF692G6-420B1 (Mini-ITX /1 pair support Bypass LAN)                                                                                                                                                                                |                     |                     |                                     |                                                 |
| Part No         | Standard                                                                                                                                                                                                                                                                                           | WIFI                | Bypass LAN          | Expansion 4 ports LAN<br>PCI-E Card | Bypass LAN+ Expansion<br>4 ports LAN PCI-E Card |
|                 | – HBJC141F692-335B                                                                                                                                                                                                                                                                                 | – HBJC141F692W-335B | – HBJC141F692B-335B | – HBJC141F692-33G4                  | – HBJC141F692B-33G4                             |
|                 | – HBJC141F692-420B                                                                                                                                                                                                                                                                                 | – HBJC141F692W-420B | – HBJC141F692B-420B | – HBJC141F692-42G4                  | – HBJC141F692B-42G4                             |
| BIOS            | – AMI 128MB SMT Flash ROM                                                                                                                                                                                                                                                                          |                     |                     |                                     |                                                 |
| CPU/Chipset     | – INTEL® Apollo Lake N3350/N4200 Processor                                                                                                                                                                                                                                                         |                     |                     |                                     |                                                 |
| Memory          | – 1 * SO-DIMM slots DDR3L-1866MHz up to 8GB                                                                                                                                                                                                                                                        |                     |                     |                                     |                                                 |
| Storage         | – 1 * 2.5" SATA3 6Gb/s internal drive bay<br>– 1 * Full-size mSATA/mini-PCI Express shared slot                                                                                                                                                                                                    |                     |                     |                                     |                                                 |
| Network         | – 6 * Intel i211AT Gigabit LAN<br>– 1 * Full-size mini-PCIE slot (802.11 b/g/n + BT 4.0 installed in WIFI model)                                                                                                                                                                                   |                     |                     |                                     |                                                 |
| Rear Panel I/O  | – 1 * Power SWITCH<br>– DC JACK                                                                                                                                                                                                                                                                    |                     |                     |                                     |                                                 |
| Front Panel I/O | – 6 * RJ45<br>– 2 * USB3.0<br>– 1 * RS232 (RJ45 TYPE)<br>– 1 * PW LED, 1 * Alarm LED<br>– 1 * HDMI ( <a href="#">Not assembled when shipped, wire placed in the parts box</a> )<br>– 1 * GPIO ( <a href="#">Not assembled when shipped, wire placed in the parts box</a> )<br>– 2 * COM (optional) |                     |                     |                                     |                                                 |
| Power Source    | – AC 90–240V input_DC12V-5A-60W out / FSP Adapter                                                                                                                                                                                                                                                  |                     |                     |                                     |                                                 |
| Compliance      | – CE, FCC, RoHS                                                                                                                                                                                                                                                                                    |                     |                     |                                     |                                                 |
| Temperature     | – Operating Temperature: 0 ~ 40° C<br>– Storage Temperature: -10 ~ 70° C                                                                                                                                                                                                                           |                     |                     |                                     |                                                 |
| Dimensions      | – 330 (W) x 192 (D) x 44 (H) mm                                                                                                                                                                                                                                                                    |                     |                     |                                     |                                                 |
| Packing         | – Net Weight: 1.6KG<br>– Gross Weight: 2.6KG<br>– Color Box dimension: 406 (W) * 148 (D) * 380 (H) mm                                                                                                                                                                                              |                     |                     |                                     |                                                 |

---

|            |                           |
|------------|---------------------------|
| OS Support | – Windows 10, Linux       |
| Warranty   | – 2 Year limited warranty |