

149.00 EUR

incl. 19% VAT, plus [shipping](#)

- DDR-II !
- FANLESS !
- 1.2 Ghz !
- 6W !



This board is based on the latest VIA C7 architecture.

J7F2EDEN12G Specifications	
Processor	VIA C7 1.2 GHz processor
Chipset	VIA CN700 north bridge VIA VT8237R south bridge
System Memory	1 DDR2 400/533 DIMM Up to 1GB memory size
VGA	Integrated VIA UniChrome AGP graphics
Expansion Slots	1 PCI
Onboard IDE	4 Ultra DMA 133
Onboard Serial ATA	2 SATA connectors
Onboard Floppy	1 Floppy Port
Onboard USB	8 USB 2.0
Onboard LAN	VIA 6103 10/100
Onboard Audio	ALC655 6 channel AC'97 codec
Onboard TV Out	VIA VT1622A TV encoder
Onboard 1394	IEEE 1394
Back Panel I/O	1 1394 1 RCA video 1 VGA port 2 USB 2.0 1 LAN port 2 IEEE 1394 ports 1 serial ports 1 PS2 mouse port 1 PS2 keyboard port 3 audio jacks: line-out, line-in, and mic-in

Onboard I/O Connectors	3 USB 2.0 connectors for 6 USB ports
	1 parallel port
	1 VGA port
	2 serial ports
	1 PS2 keyboard connector
	1 PS2 mouse connector
	1 floppy port
	Line-in/out/MIC audio ports
BIOS	Award BIOS LPC 4Mbit Flash memory
System Monitoring & Management	CPU temperature
	Modem ring wake up
	RTC Alarm
	Keyboard power on
	System temperature
	System voltage
	Fan speed
Operating Humidity	0% ~ 95% (relative humidity; non-condensing)
Form Factor	Mini-ITX (17cm x 17cm)
Includes	ATA 133 flat cable (40 wire, 80 conductor, 3 connectors)
	CD
	SATA Cable
	Floppy Cable